

Bantam™ Hand Held Core Drills

No Set-up Required

**Increase Your
Daily Production**

Easy To Use

**Internal Slip Clutch
for Optimal Safety**



Make Difficult Drilling Jobs EASY!



**250 BARBER AVENUE
WORCESTER, MA 01606-2435
TEL. (508) 853-3991 • FAX (508) 793-9864**



Dry Drilling

← **Model RW300DN**
Hand Held for Dry Drilling Block & Brick up to 3" Diameter

Model RW500DN →
Hand Held for Wet Drilling Concrete up to 5" Diameter, Brick & Hollow Block up to 6" Diameter



Wet Drilling

The RW500DN Can Be Used for Stationary Drilling With The Optional Drill Stand



Model RW500DNS
Drill Stand
Use Vertical or Tilted up to 45 degrees



Technical Specifications	RW300DN Dry Drilling	RW500DN Wet Drilling
Amperage	12-Amp	17-Amp
Voltage	110-Volt	110-Volt
Maximum Drill Diameter	3"	5" Wet / 6" Dry
Loaded Speeds	2000 RPM	600-RPM 1300-RPM 2800-RPM
Spindle	5/8"-11 UNC and 1 1/4" - 7 UNC included	5/8"-11 UNC and 1 1/4" - 7 UNC included
Weight	7 lbs.	16 lbs.